
Job Name:_





PRODUCT DESCRIPTION

This outdoor collection is cast in concrete for maximum durability in harsh climates such as coastal environments. Available in your choice of White or Grey Aggregate, both are powered by dual integrated LED boards for efficient and long life operation.



MEASUREMENTS

DIMENSION MAX OAH HANGING WEIGHT

LAMPING

INPUT VOLTAGE LUMENS BULB **BULB INCLUDED** DIMMABLE CRI COLOR_TEMP

: 7.75" W x 22" H x 3.5" Ext : 6.25" W x 11.5" H

- - : 840 Rated (680 Del.)
 - : 6W LED AC Integrated , 12W Total
 - : Electronic Low Voltage (ELV)
 - : 80 CRI
- LIGHTING_DIRECTION

: 12.8 lb

- :120V

- : (Integrated)
- : 3000K
- : Down





MATERIAL Concrete, Aluminum

RATINGS cETLus Wet Location ADA



ADDITIONAL

INSTALL UP/DOWN: Up SLOPE: RATED LIFE 35000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Job Name Job Type: Quantity: Comments

Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

StudioMlighting.com - 1.626.956.4209