LENCIR LED | SURFACE MOUNT


SM567720 / SM567722 / SM567724

- Die Cast Aluminum
- Size options between 4.5", 6.25" and 9"
- Ultra thin 0.5" H
- Approved for use in closets and storage spaces
- Suitable for Closets according to NEC Section 410.8 & 410.16
- \bullet Available in White (WT), Bronze (BZ), and Satin Nickel (SN)
- Triac Dimmable with Electronic Low Voltage Dimmers • Easy to install: fits in 3-0 and 4-0 Outlet Box
- Easy to Install: tits in 3-0 and 4-0 Out
- Edge-Lit LED TechnologySuitable for Wet Location
- ETL/cETL IP65



PRODUCT DESCRIPTION

Lencir was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Lencir brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.



MEASUREMENTS

 MODEL
 DIMENSION

 SM567720
 4.5"L x 4.5"W x 0.5"H

 SM567722
 6.25"L x 6.25"W x 0.5"H

 SM567724
 9"L x 9"W x 0.5"H

LAMPING

			LUMENS	COL		
MODEL	BULB TYPE	CRI	INIT DEL	TEMP.	DIMMABLE	I
SM567720	10W PCB LED (Integrated)	90+	700 600	3000K	ELV	
SM567722	15W PCB LED (Integrated)	90+	1050 900	3000K	ELV	
SM567724	20W PCB LED (Integrated)	90+	1400 1200	3000K	ELV	

HANGING

WEIGHT 0.99 lb

1.21 lb

1.80 lb

Always consult a qualified electrician before installing any lighting product



For Modifications or Customizations, please email contract@studiomlighting.com

For Sample Request, please email order@studiomlighting.com with subject line: "Sample Order_[Project Name]/[Specifier/Designer]" All Samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments:

FINISHES OPTIONS:

White (WT) Bronze (BZ) Satin Nickel (SN)



MATERIAL: Die Cast Aluminum PMMA Acrylic Diffuser

AVAILABLE SIZES: 4.5" | 6.25" | 9"

RATINGS:

INPUT

120V

120V

120V

ETL/CETL IP65 Wet Location Energy Star Title 24 JA8 compliant ADA Closets Rated: NEC 410.8 & 410.16



ADDITIONAL: RATED LIFE: 50,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) PHOTOMETRIC: Report Found Online