# **CAVUS** | Recessed Downlight

# SM567794 / SM567796

- LED 3000K, CRI 90+
- 4 inch and 6 inch Recessed Can Subtitute
- UL Outlet Box fitted on fixture
- Dimmable with Triac Dimmer
- Good for new constrution and remodels
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Indirect lighting into cove for soft-even illumination
- IC-Rated for direct contact with insulation
- Damp Location Rated
- Fire Rated
- Title 24
- ETL/cETL



A.	News

Job Name:	Job Type:
Quantity:	Comments:








**57790**Cove Rough in Plate for New Construction Hanging weight: 10lb)

# PRODUCT DESCRIPTION

Maxim's Cove recessed downlight series offers a IC Airtight UL rated Outlet Box that is fitted to the fixture for easy installation without the use of a recessed housing. To reduce glare that is associated with other recessed downlights, the Cove uses an innovative concave lens that directs the light upward and is then reflected back down offering even and abundant illumination. Fire Rated and available in standard 120V, Triac dimming, with Color Temperature of 3000K, and CRI of 90+, the Cove is one of the most versatile downlights in the market.



# 

## **MEASUREMENTS**

DIMENSION
4.75"D x 3.25"H
6.75"D x 3.75"H

# **LAMPING**

MODEL	BULB TYPE
57794	9W PCB LED (Integrated)
57796	12W PCB LED (Integrated)

BP Height	нсо	HANGING WEIGHT
1.85"H	3.30"	0.55 lb
1.85"H	3.80"	0.77 lb

CRI	LUMENS	COL TEMP.	DIMMABLE	INPUT
90+	540	3000K	Triac CL	120V
90+	720	3000K	Triac CL	120V

# FINISHES OPTIONS:

White (WT)

# MATERIAL:

Aluminum

## **AVAILABLE SIZES:**

4" | 6"

# RATINGS:

ETL/cETL IC Airtight Fire Rated Damp Location Energy Star Title 24

**ADDITIONAL:** 

Closets Rated: NEC 410.8 & 410.16







## KAIED LIFE: 40

RATED LIFE: 40,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) PHOTOMETRIC: Report Found Online LIGHTING DIRECTION: Down

Always consult a qualified electrician before installing any lighting product

STUDIO M