# SOLSTICE | FANDELIER SM660006SN

- FTL/CETL
- Title 20 listed
- LED 3000K
- Suitable for Dry location
- Wall mountable (remote control included)




# **PRODUCT DESCRIPTION**

The Solstice collection houses three innovatively curved fan blades within a cage of artfully bent Satin Nickel channel to create a classic form in light. Its architecturally contemporary styling is paired with high-powered LED lighting making it functional and fantastic for transitional and modern settings.

- Always consult a qualified electrician before installing any lighting product
- Installation Requirements:

Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding at least 35 lbs



**MEASUREMENTS** 

DIMENSIONS : 34.25"D x 23.5"H HANGING WEIGHT : 8.19 lb BLADE : 3 Blades with 22" span **BLADE PITCH** : Varying BLADE TO CEILING : 14"H

### LAMPING

LUMENS

BULB

CRI

INPUT VOLTAGE :120V : 5200 : (8) 7W PCB LED (Integrated), 56W Total DIMMABLE : Yes : 80+ COLOR TEMP : 3000K MOTOR TYPE : DC Motor

#### AIRFLOW SPEEDS : 6 AIRFLOW CFM : 5057 ELECTRICITY USE · 31 90W AIRFLOW EFFICIENCY: 158.5

# 

For Modifications or Customizations, please email contract@studiomlighting.com

For Sample Request, please email order@studiomlighting.com with subject line: "Sample Order\_[Project Name]/[Specifier/Designer]" All Samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments:

# FINISHES OPTIONS:

Satin Nickel

# MATERIAL:

Steel Polypropelene Fan Blades Aluminum

### INCLUDES

• Wall Mountable Remote Control

1 x 8" Downrod

### **DOWNROD OPTIONS**

- 18" (FRD0118SN)
- 24" (FRD0124SN)
- 30" (FRD0130SN) • 36" (FRD0136SN)

## **RATINGS:**

ETL CETL Dry Location Title 20



**ADDITIONAL:** RATED LIFE: 35,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) LIGHTING DIRECTION: Up