CANDELLA | FANDELIER SM660012CHBGLD

• FTL/CFTL

- Suitable for Damp location
- Title 20 listed
- LED 2700K
- Wall mountable (remote control included)
- Frosted CA LED bulbs included




PRODUCT DESCRIPTION

The Candella Fandelier is a stunning reflector-style chandelier complete with a silent, yet powerful adjustable speed fan. Candella features three signature curved fan blades outlined by a period inspired metal framework finished in a hand-painted Chestnut Bronze. The included LED candelabra bulbs illuminate Gold painted reflectors offering brighter and warmer light throughout the space. It is the perfect package for any dining room, kitchen or outdoor living area. Timeless and elegant, it pairs well with a wide variety of styles and colors, making it compatible with almost any space.

• Always consult a qualified electrician before installing any lighting product

• Installation Requirements:

Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding at least 35 lbs



MEASUREMENT	S
-------------	---

DIMENSIONS : 31.25"D x 25.75"H CANOPY : 6.75"D x 2.75"H HANGING WEIGHT : 23.94 lb : 3 Blades with 22" span BLADE **BLADE PITCH** : Varying BLADE TO CEILING : 15"H

LAMPING

INPUT VOLTAGE :120V LUMENS : 1988 Rated (1680 Del.) BULB : (6) 4W CA LED (Integrated), 24W Total DIMMABLE : Yes : 80+ CRI COLOR TEMP : 2700K MOTOR TYPE : DC Motor

AIRFLOW

SPEEDS :6 AIRFLOW CFM : 5057 FLECTRICITY LISE · 31 90W AIRFLOW EFFICIENCY: 158.5

For Modifications or Customizations, please email contract@studiomlighting.com

For Sample Request, please email order@studiomlighting.com with subject line: "Sample Order [Project Name]/[Specifier/Designer]" All Samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments:

FINISHES OPTIONS:

Chestnut Bronze/Gold (CHBGLD)

MATERIAL:

Steel Polypropelene Fan Blades

INCLUDES

Wall Mountable Remote Control

• 1 x 13.375" Downrod

DOWNROD OPTIONS

- 18" (FRD0118CHB)
- 24" (FRD0124CHB)
- 30" (FRD0130CHB) • 36" (FRD0136CHB)

RATINGS: ETL CETL Damp Location Title 20



ADDITIONAL: RATED LIFE: 20,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F)