

PRODUCT DESCRIPTION

Linear EE collection's commercial grade energy efficient lighting features linear frames of metal finished in Satin Nickel and White acrylic diffusers. High Power Factor ballasts allow for commercial applications and the fluorescent light source ensure low maintenance and energy cost savings. Specific styles of Linear EE are also available with a LED light source in the Linear LED collection.



MEASUREMENTS

DIMENSION BACK PLATE HANGING WEIGHT

LAMPING

INPUT VOLTAGE LUMENS

BULB

BULB INCLUDED

DIMMABLE

: 6.02 lb

: 36" W x 6" H x 4" Ext

: 120V : 4,300 Rated

: 25W Fluorescent Med Bi Pin T8, 50W Total

: 2.74" W x 35.17" H x 2.25" HCO

: (Not Included)

: No

FINISHES OPTION



GLASS

White WT

MATERIAL

Metal

RATINGS

cETLus Damp Location CA Title 24 ADA







ADDITIONAL

INSTALL UP/DOWN: All INCANDESCENT WATTS: 436 RATED LIFE 10000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com
Sample Request: Please email order@studiomlighint.com with subject line
"Sample Order_ [Project Name] / [Specifier/Designer]"
All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments