






PRODUCT DESCRIPTION

A central, cylinder diffuser of opal white acrylic diffuses LED lighting within a cavity of thin ribbed glass of various lengths. Both imaginative and functional, the bright pendants encase an additional down light recessed within a Polished Chrome, Naturally Aged Brass or Matte Black housing casting light downward.



MEASUREMENTS

DIMENSION : 1.5" L x 1.5" W x 10.75" H
MAX OAH : 133.25" OAH

CANOPY : 4.75" W x 1.75" H x 4.75" L

HANGING WEIGHT : 1.98 lb

LAMPING

INPUT VOLTAGE

LUMENS : 600 Rated (450 Del.)

BULB : 7.5W LED PCB Integrated, 8W Total

: 120-277V

BULB INCLUDED : (Integrated)
DIMMABLE : Universal 3-in-1
CRI : 90 CRI
COLOR_TEMP : 3000K

FINISHES OPTION

Black (BK)

Natural Aged Brass (NAB)

Polished Chrome (PC)

GLASS

Clear Ribbed 144

MATERIAL

Steel, Aluminum, Glass

RATINGS

cETLus Dry Location





ADDITIONAL

RATED LIFE 35000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Job Name:	Job Type:
Quantity:	Comments