Quantity:





PRODUCT DESCRIPTION

*max overall height

A central, cylinder diffuser of opal white acrylic diffuses LED lighting within a cavity of thin ribbed glass of various lengths. Both imaginative and functional, the bright pendants encase an additional down light recessed within a Polished Chrome, Naturally Aged Brass or Matte Black housing casting light downward.

n ilin

4.75 1.75″⊏ 133.25″ 11 1.5

MEASUREMENTS DIMENSION MAX OAH CANOPY

HANGING WEIGHT LAMPING INPUT VOLTAGE LUMENS BULB BULB INCLUDED DIMMABLE CRI COLOR_TEMP

: 1.5" L x 1.5" W x 10.75" H : 133.25" OAH : 4.75" W x 1.75" H x 4.75" L : 1.98 lb

:120-277V : 600 Rated (450 Del.) : 7.5W LED PCB Integrated , 8W Total : (Integrated) : Universal 3-in-1 : 90 CRI : 3000K

FINISHES OPTION



Natural Aged Brass (NAB)

Polished Chrome (PC)

GLASS Clear Ribbed 144

MATERIAL Steel, Aluminum, Glass

RATINGS

cETLus Dry Location



ADDITIONAL RATED LIFE 35000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation. Job Name Job Type: Quantity: Comments