

PRODUCT DESCRIPTION

Channels of Polished Chrome stainless steel are formed by hand into an irregular shaped ring. LED modules are then recessed into the pendant frame and diffused through beveled crystals, bouncing light off the irregular surfaces to create a unique lighting effect. Coordinating non-lighted mirror pairs well with modern decor.



MEASUREMENTS DIMENSION MAX OAH HANGING WEIGHT LAMPING

INPUT VOLTAGE LUMENS BULB **BULB INCLUDED** DIMMABLE CRI COLOR_TEMP

: 26.75" L x 26.75" W x 34" H : 55.5" OAH : 22 lb

:120V : 2,200 Rated : 2W LED PCB Integrated , 48W Total : (Integrated) : Triac CL : 80+ CRI : 3000K

FINISHES OPTION



MATERIAL Stainless Steel

RATINGS cETLus Dry Location



ADDITIONAL

ADJUSTABLE SLOPE: 30 RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Job Name Job Type: Quantity: Comments

Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

StudioMlighting.com - 1.626.956.4209





Job Type:_

