Quantity:







PRODUCT DESCRIPTION

Soft oval forms offer a modern and playful touch to this LED wall mounted sconce. The face of the fixture is a light guided White acrylic diffuser that even illuminates the edge-lit LED light source. The sleek shape is made even more attractive by the bright illumination provided by the fixture itself. Great for use in bathrooms or corridors, the fixture is ADA compliant and available in 4 lengths. A recessed housing behind the fixture not only mounts the fixture with an attractive extension that makes it appear to be floating off the wall, but it also features a 5-step color temperature select switch allowing you to discreetly adjust the LED lighting to 5 settings ranging from a warmer 2700K to 3000-3500-4000 and daylight white 5000K. These additional product features thereby give more latitude to the design applications without special requests.

> **MEASUREMENTS** DIMENSION BACK PLATE HANGING WEIGHT LAMPING INPUT VOLTAGE LUMENS BULB **BULB INCLUDED** DIMMABLE CRI COLOR_TEMP LIGHTING_DIRECTION

: 30" W x 5" H x 2.5" Ext : 4" W x 19.5" H x 15" HCO : 4.84 lb

:120V : 3,000 Rated (1,700 Del.) : 25W LED AC Integrated , 30W Total : (Integrated) : Triac or ELV : 90 CRI : CCT Select 5KK : Backlit

FINISHES OPTION



MATERIAL

Aluminum, Polycarbonate

RATINGS

CETLUS Damp Location ADA



ADDITIONAL

INSTALL UP/DOWN: Horizontal/Vert RATED LIFE 35000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]"

All samples are subject to Studio M approval and must show proof of pr	pipet and/or explanation
All samples die subject to studio in approval and must show proof of pr	olect analor explanation.

Job Name:	Job Type:
Quantity:	Comments