

Job Name:

Job Type:


Quantity:_



Comments:

PRODUCT DESCRIPTION

Introducing a new take on the now classically modern LED ring, large illuminated spheres act as "nodes" to support the tapered aluminum channel while also providing additional down light. Featuring a CCT selectable switch, the collection conveniently allows end users to select from warmer white light to energizing bright white lighting in 5 color temperature options. The convenient functionality is matched with its performance, meeting California's JA8 Title 24 requirements. Rated to deliver higher lumens per watt and power sources that supports range voltage input and 3 in one dimming, this product is designed to meet the requirements of both home and commercial projects.



*max overall height

MEASUREMENTS DIMENSION MAX OAH CANOPY

HANGING WEIGHT LAMPING INPUT VOLTAGE LUMENS BULB

BULB INCLUDED CRI COLOR_TEMP : 32" L x 32" W x 2.75" H : 108" OAH : 7" W x 1.5" H x 7" L : 4.12 lb

: 120-277V : 3,200 Rated (2,800 Del.) : 40W LED CCT Select PCB , 40W Total : (Integrated) : 90 CRI : 27-30-35-40-50K

FINISHES OPTION



MATERIAL Aluminum, Steel

RATINGS Dry Location CA Title 24



ADDITIONAL

OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments