



Comments:

PRODUCT DESCRIPTION

Constructed of double thick aluminum which has a hammered interior finish polished so to not only be beautiful but multiply the lumen output. High polish enamel paints finish the exterior for the ultimate reflective surface. The larger sizes are fitted with commercial grade LED and multi-volt input drivers that dim with both ELV and 0-10V functions.



*max overall height

MEASUREMENTS DIMENSION MAX OAH

CANOPY HANGING WEIGHT LAMPING

INPUT VOLTAGE LUMENS BULB BULB INCLUDED DIMMABLE

BULB INCLUDED DIMMABLE CRI COLOR_TEMP : 14" L x 14" W x 8" H : 129" OAH : 6" W x 1" H x 6" L : 2.88 lb

Job Name:_

Job Type:_

Quantity:

: 120V : 1,500 Rated (720 Del.)

- : 15W LED PCB Integrated , 15W Total : (Integrated)
- : ELV or Triac CL
- : 90 CRI
 - : 3000K

FINISHES OPTION



MATERIAL Aluminum

RATINGS CETLUS

Dry Location



ADDITIONAL

SLOPE: 30 RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments