Job Type:_



PRODUCT DESCRIPTION

Translucent acrylic panels dotted to guide indirect LED strips integrated into the body of the fixture. The angular forms of the pendants create a strikingly modern display of light that is both airy and voluminous. An additional LED GU10 bulb is recessed at the bottom of the fixture for additional functional light. Available in Satin Brass or Matte Black finishes.



MEASUREMENTS DIMENSION

MAX OAH CANOPY HANGING WEIGHT LAMPING

INPUT VOLTAGE LUMENS BULB BULB INCLUDED DIMMABLE CRI COLOR_TEMP : 26" L x 26" W x 18" H : 61" OAH : 4.75" W x 0.75" H x 4.75" L : 5.5 lb

: 120V : 3,760 Rated (1,880 Del.) : 10W LED LED , 47W Total : (Integrated) : ELV or Triac CL : 90 CRI

: 3000K

FINISHES OPTION

Black (BK)

Natural Aged Brass (NAB)

GLASS Patterned Acrylic 133

MATERIAL Steel + Aluminum+Acrylic

RATINGS CETLUS

Dry Location



ADDITIONAL

SLOPE: 15 RATED LIFE 40000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments