Job Name:_____

Quantity:





PRODUCT DESCRIPTION

Elongated tubes of LED light are housed in incredibly small 1" diameter aluminum and suspended by nearly invisible support cables. Engineered to connect the various lengths end-to-end or with use of the rigid, angled adapters, adds endless applications for creativity and function. Each length includes a power feed within a surface mounted canopy and non-electrical support cables that standoff using ceiling anchors. The continuous run pendants in this series are a welcome convenience for commercial applications. Lengths range from 36" to impressive 96" long. Individually, the fixtures provide ample lighting downward with minimal disruption to the architectural sight lines of a space. Available in Black, White, and brushed Aluminum finishes these are exemplary streamlined forms with functional purpose.



MEASUREMENTS

DIMENSION MAX OAH CANOPY HANGING WEIGHT LAMPING

INPUT VOLTAGE

LUMENS BULB BULB INCLUDED DIMMABLE CRI COLOR_TEMP : 38.5" L x 1.5" W x 1.25" H : 121" OAH : 5" W x 1" H x 5" L : 3.03 lb

: 120-277V : 2,250 Rated (1,800 Del.) : 28W LED PCB Integrated , 28W Total : (Integrated) : Universal 3-in-1 : 90 CRI : Select 30/35/40K

FINISHES OPTION



GLASS Frosted 90

MATERIAL Acrylic, Aluminum

RATINGS CETLUS

Dry Location



ADDITIONAL RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation. Job Name: Job Type: Quantity: Comments