






### PRODUCT DESCRIPTION

Elongated tubes of LED light are housed in incredibly small 1" diameter aluminum and suspended by nearly invisible support cables. Engineered to connect the various lengths end-to-end or with use of the rigid, angled adapters, adds endless applications for creativity and function. Each length includes a power feed within a surface mounted canopy and non-electrical support cables that standoff using ceiling anchors. The continuous run pendants in this series are a welcome convenience for commercial applications. Lengths range from 36" to impressive 96" long. Individually, the fixtures provide ample lighting downward with minimal disruption to the architectural sight lines of a space. Available in Black, White, and brushed Aluminum finishes these are exemplary streamlined forms with functional purpose.



# **MEASUREMENTS**

DIMENSION : 93.7" L x 1.5" W x 1.25" H MAX OAH : 121" OAH : 4.5" W x 1.25" H x 16" L CANOPY

HANGING WEIGHT LAMPING

INPUT VOLTAGE : 120-277V

**LUMENS** : 5,250 Rated (4,200 Del.)

BULB : 68W LED PCB Integrated, 68W Total BULB INCLUDED : (Integrated)

: 6.5 lb

DIMMABLE : Universal 3-in-1

: 90 CRI

**CRI** 

COLOR\_TEMP : Select 30/35/40K

### **FINISHES OPTION**



White (WT)

#### **GLASS**

Frosted 90

#### MATERIAL

Acrylic, Aluminum

## **RATINGS**

cETLus Dry Location





#### **ADDITIONAL**

RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.

	Job Name:	Job Type:
	Quantity:	Comments