






PRODUCT DESCRIPTION

A box of UV-rated acrylic is constructed of precise miter cut corners and silk screened white on its interior to form a tower of evenly distributed LED illumination. For wet locations, the LED light source is completely sealed and provides softer omnidirectional illumination to add security and sufficiently brighten spaces. The die cast aluminum frame is finished in a black outdoor rated powder coat for longer lasting color in outdoor settings.



*height from center of outlet to the top of the fixture

MEASUREMENTS

DIMENSION : 8" W x 15" H x 4" Ext **BACK PLATE** : 8" W x 13.4" H x 7.5" HCO

HANGING WEIGHT : 5.03 lb

LAMPING

INPUT VOLTAGE : 120V

LUMENS : 1,200 Rated (1,170 Del.)

BULB : 15W LED PCB Integrated, 15W Total

BULB INCLUDED : (Integrated) DIMMABLE : Y

CRI : 90 CRI COLOR_TEMP : 3000K LIGHTING_DIRECTION : Omni

FINISHES OPTION



GLASS

White 01

MATERIAL

Aluminum

RATINGS

cETLus Wet Location ADA







ADDITIONAL

INSTALL UP/DOWN: Up/Down RATED LIFE 35000 Hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.

Job Name:	Job Type:
Quantity:	Comments