

PRODUCT DESCRIPTION

White Acrylic diffusers are miter cut and beveled along the edge of these mirror frames allowing for wider, and brighter lighting. Robust in size, these mirrors feature excellent construction and 2CCT light selection using a discreet touch switch on the frames edge. Hardwire the mirrors to a dimmer switch to control the brightness and the memory function on the LED will recall the chosen color temperature of the previous setting.

> MEASUREMENTS DIMENSION HANGING WEIGHT LAMPING INPUT VOLTAGE LUMENS BULB BULB INCLUDED DIMMABLE CRI COLOR_TEMP

: 48" W x 30" H x 2.25" Ext : 35.2 lb

- : 120V
- : 5,800 Rated (2,030 Del.)
- : 58W LED DC Integrated , 58W Total
- : (Integrated) : Touch Switch
- : 90 CRI
 - : 3000-4000K

FINISHES OPTION



MATERIAL Aluminum, PC , Glass

RATINGS cETLDamp Location ADA



ADDITIONAL

SLOPE: RATED LIFE 35000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Job Name: Job Type: Quantity: Comments

Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

StudioMlighting.com - 1.626.956.4209