

RAIL LED | Bath Vanity

SM562100 / SM562102 / SM562103 / SM562104


- ETL, cETL IP65
- Suitable for damp locations
- CRI 90+
- Dimmable with Triac Dimmer
- Energy Star
- Title 24 JA8 Compliant

Job Name:	Job Type:
Quantity:	Comments:



PRODUCT DESCRIPTION

Tubular shaped White acrylic diffusers mount to frames of Polished Chrome, Satin Nickel, or Black. Powered by 3000K LED these fixtures work well in a variety of contract applications.



MEASUREMENTS

MODEL	DIMENSION	HANGING WEIGHT
SM562100	18"L x 4.75"H x 2.50"EXT	0.70 LB
SM562102	24"L x 4.75"H x 2.50"EXT	0.85 LB
SM562103	30"L x 4.75"H x 2.50"EXT	1.10 LB
SM562104	36"L x 4.75"H x 2.50"EXT	1.30 LB

LAMPING

MODEL	BULB TYPE	CRI	LUMENS		COL TEMP.	DIMMABLE	INPUT
			RATED	DEL			
SM562100	(1) 12W LED (Integrated)	90+	1140	930	3000K	Triac Dimmer	120V
SM562102	(1) 16W LED (Integrated)	90+	1520	1400	3000K	Triac Dimmer	120V
SM562103	(1) 20W LED (Integrated)	90+	1900	1690	3000K	Triac Dimmer	120V
SM562104	(1) 24W LED (Integrated)	90+	2280	2040	3000K	Triac Dimmer	120V

FINISHES OPTIONS:

- Satin Nickel (SN)
- Polished Chrome (PC)
- Black (BK)



MATERIAL:

Aluminum + Acrylic

RATINGS:

- ETL cETL IP65
- Damp Location
- Energy Star
- Title 24 JA8 Compliant
- ADA
- Dimmable



ADDITIONAL:

- RATED LIFE : 50,000 hours
- INSTALL UP/DOWN: Both
- OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product

STUDIO•M

For Modifications or Customizations, please email contract@studiomlighting.com

For Sample Request, please email order@studiomlighting.com with subject line: "Sample Order_[Project Name]/[Specifier/Designer]"

All Samples are subject to Studio M approval and must show proof of project and/or explanation.

StudioMlighting.com - 626.956.4209