
Quantity:_

Job Type:_



PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Choose from a variety of sizes, shapes that are sharply angled or smoothly sloping, and various photocell and motion sensor options. Also available with enabled switch to toggle between 5 light Color Temperature settings, this popular sconce has even more versatility. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor-rated powder coat finishes.



*height from center of outlet to the top of the fixture



5.5" BULB INCLUDED DIMMABLE CRI

BULB

COLOR_TEMP LIGHTING_DIRECTION

MEASUREMENTS

HANGING WEIGHT

INPUT VOLTAGE

DIMENSION

BACK PLATE

LAMPING

LUMENS

: 5.5" W x 7" H x 4" Ext : 4.25" HCO : 2.31 lb

- : 120-277V
- : 1,050 Rated (750 Del.)
- : 15W LED DC Integrated , 15W Total
- : (Integrated) : Triac or ELV at 120V
- : 90 CRI
- : 3000K
 - : Down

FINISHES OPTION



MATERIAL Aluminum

RATINGS cETLus Wet Location ADA



ADDITIONAL

INSTALL UP/DOWN: Down SLOPE: RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments