Job Type:_



PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Choose from a variety of sizes, shapes that are sharply angled or smoothly sloping, and various photocell and motion sensor options. Also available with enabled switch to toggle between 5 light Color Temperature settings, this popular sconce has even more versatility. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor-rated powder coat finishes.

| MEASUREMENTS | |
|--------------------|--------------------------------------|
| DIMENSION | : 7" W x 4.5" H x 3.5" Ext |
| BACK PLATE | : 2.25" HCO |
| HANGING WEIGHT | : 1.51 lb |
| LAMPING | |
| INPUT VOLTAGE | : 120-277V |
| LUMENS | : 880 Rated (820 Del.) |
| BULB | : 15W LED PCB Integrated , 15W Total |
| BULB INCLUDED | : (Integrated) |
| DIMMABLE | : Only at 120V with ELV |
| CRI | : 80 CRI |
| COLOR_TEMP | : 3000K |
| LIGHTING_DIRECTION | : Down |
| | |

FINISHES OPTION



MATERIAL Aluminum +Acrylic

RATINGS

cETLus Wet Location ADA



ADDITIONAL

INSTALL UP/DOWN: Down SLOPE: PHOTOCELL RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Job Name: Job Type: Quantity: Comments

Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.