Job Type:_



PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Choose from a variety of sizes, shapes that are sharply angled or smoothly sloping, and various photocell and motion sensor options. Also available with enabled switch to toggle between 5 light Color Temperature settings, this popular sconce has even more versatility. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor-rated powder coat finishes.

MEASUREMENTS	
DIMENSION	: 7" W x 4.5" H x 3.5" Ext
BACK PLATE	: 2.25" HCO
HANGING WEIGHT	: 1.51 lb
LAMPING	
INPUT VOLTAGE	: 120-277V
LUMENS	: 880 Rated (820 Del.)
BULB	: 15W LED PCB Integrated , 15W Total
BULB INCLUDED	: (Integrated)
DIMMABLE	: Only at 120V with ELV
CRI	: 80 CRI
COLOR_TEMP	: 3000K
LIGHTING_DIRECTION	: Down

FINISHES OPTION



MATERIAL Aluminum +Acrylic

RATINGS

cETLus Wet Location ADA



ADDITIONAL

INSTALL UP/DOWN: Down SLOPE: PHOTOCELL RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments