Comments:

## **PRODUCT DESCRIPTION**

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Choose from a variety of sizes, shapes that are sharply angled or smoothly sloping, and various photocell and motion sensor options. Also available with enabled switch to toggle between 5 light Color Temperature settings, this popular sconce has even more versatility. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor-rated powder coat finishes.

> **MEASUREMENTS** DIMENSION BACK PLATE HANGING WEIGHT : 2.5 lb LAMPING INPUT VOLTAGE : 120-277V LUMENS BULB **BULB INCLUDED** : (Integrated) DIMMABLE : 90 CRI CRI COLOR\_TEMP LIGHTING\_DIRECTION : Down

: 9" W x 8" H x 4" Ext : 9" W x 8" H x 4" HCO

: 2,000 Rated (1,250 Del.) : 20W LED DC Integrated , 20W Total : Triac or ELV at 120V : 22-27-30-35-40K





MATERIAL Aluminum, Glass

RATINGS cETLus

Wet Location ADA



## ADDITIONAL

INSTALL UP/DOWN: Down SLOPE: RATED LIFE 25000 Hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order\_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments