# **COVE I** Recessed Downlight

#### SM567792 / SM567793 / SM567794 / SM567796 / SM567797 / SM567798

- LED 3000K or 4000K Options
- · 4 inch and 6 inch Recessed Can Substitute
- UL Outlet Box fitted on fixture
- Dimmable with Triac Dimmer
- Good for new construction and remodels
- Suitable for closets according to NEC Section 410.8 & 410.16
- Indirect lighting into cove for soft-even illumination
- IC-Rated for direct contact with insulation
- Damp Location Rated
- Title 24
- ETL/cETL
- CRI 90+













SM567790 Cove Rough in Plate for New Construction (Hanging weight: 10lb)

#### PRODUCT DESCRIPTION

Maxim's Cove recessed downlight series offers an IC Airtight UL rated Outlet Box that is fitted to the fixture for easy installation without the use of a recessed housing. To reduce glare that is associated with other recessed downlights, the Cove uses an innovative concave lens that directs the light upward and is then reflected back down offering even and abundant illumination. The Cove is one of the most versatile downlights in the market.





# **MEASUREMENTS**

MODEL	DIMENSION	BP Height	нсо	HANGING WEIGHT		
SM567792	4.75"D x 3.25"H	1.85"H	3.30"	0.55 lb		
SM567793	4.75"D x 3.25"H	1.85"H	3.30"	0.55 lb		
SM567794	4.75"D x 3.25"H	1.85"H	3.30"	0.55 lb		
SM567796	6.75"D x 3.75"H	1.85"H	3.80"	0.77 lb		
SM567797 SM567798	6.75"D x 3.75"H 6.75"D x 3.75"H	1.85"H 1.85"H	3.30" 3.80"	0.77 lb 0.77 lb		

## **LAMPING**

		COL				
MODEL	BULB TYPE	CRI	LUMENS		DIMMABLE	INPUT
SM567792 SM567793 SM567794 SM567796 SM567797 SM567798	12K D7 6 998 flph/ [fUH/ XŁ 12W PCB LED (integrated) 9W PCB LED (integrated) 12W PCB LED (integrated) 15K D7 6 998 fintegratedŁ 15K D7 6 998 fintegratedŁ	90+ 90+ 90+ 90+ 90+ 90+	620 620 540 720 950 950	3000K 4000K 3000K 3000K 3000K 4000K	Triac CL Triac CL Triac CL Triac CL Triac CL Triac CL	120V 120V 120V 120V 120V 120V

Always consult a qualified electrician before installing any lighting product.

### FINISHES OPTIONS:

White (WT)

#### MATERIAL:

Aluminum

#### **AVAILABLE SIZES:**

4" | 6"

#### **RATINGS:**

FTL/cFTL IC Airtight Damp Location Energy Star Title 24

Closets Rated: NEC 410.8 & 410.16











## **ADDITIONAL:**

RATED LIFE: 40,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) PHOTOMETRIC: Report Found Online LIGHTING DIRECTION: Down

Modifications of Customization: Please email contract@studiomlighting.com Sample Request: Please email Order@studiomlighting.com with line "Sample Order \_ [Project Name] / [Specifier/Designer]"

All samples are subject to Studio M approval and must show proof of project and/or explanation

Job Name:	Job Type:
Quantity:	Comments