
Quantity:





PRODUCT DESCRIPTION

Step and pathway lighting suitable for interior or exterior application. Designed to install into a single gang box and is line voltage so additional transformers are not needed. Available in Aluminum, White, Black, or Bronze and both horizontal wide beam or vertical narrow beam spread.



MEASUREMENTS DIMENSION

HANGING WEIGHT LAMPING INPUT VOLTAGE LUMENS BULB BULB INCLUDED DIMMABLE CRI

COLOR_TEMP

: 3" W x 5" H x 1.75" Ext : 0.4 lb

- : 120-277V
- : 300 Rated (20 Del.)
- : 3W LED DC Integrated , 3W Total
- : (Integrated)
- : Triac
- : 80 CRI : 30-40-65K

FINISHES OPTION

Black (BK) White (WT)

MATERIAL Aluminum

RATINGS CETLus Wet Location ADA



RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



Job Name:	Job Type:
Quantity:	Comments

Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]"

All samples are subject to Studio M approval and must show proof of project and/or explanation.