Quantity:





PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Choose from a variety of sizes, shapes that are sharply angled or smoothly sloping, and various photocell and motion sensor options. Also available with enabled switch to toggle between 5 light Color Temperature settings, this popular sconce has even more versatility. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor-rated powder coat finishes.

> **MEASUREMENTS** DIMENSION MAX OAH HANGING WEIGHT LAMPING INPUT VOLTAGE LUMENS BULB **BULB INCLUDED** DIMMABLE CRI

: 3" W x 5" H x 1.5" Ext

COLOR_TEMP

: 0.53 lb

:100-277V : 300 Rated (70 Del.)

- : 3W LED DC Integrated , 3W Total
- : (Integrated)
- : N : 80 CRI
- : 3000K



Aluminum

FINISHES OPTION

Black (BK)

White (WT)

RATINGS

cETLus Wet Location ADA



ADDITIONAL

SLOPE: RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments