





## PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Choose from a variety of sizes, shapes that are sharply angled or smoothly sloping, and various photocell and motion sensor options. Also available with enabled switch to toggle between 5 light Color Temperature settings, this popular sconce has even more versatility. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor-rated powder coat finishes.

## **MEASUREMENTS**

DIMENSION : 3" W x 5" H x 1.5" Ext

MAX OAH : 0.53 lb

LAMPING . 0.331

INPUT VOLTAGE : 100-277V

LUMENS : 300 Rated (70 Del.)

BULB : 3W LED DC Integrated , 3W Total

BULB INCLUDED : (Integrated)
DIMMABLE : N

CRI : 80 CRI
COLOR\_TEMP : 3000K

## **FINISHES OPTION**



### MATERIAL

Aluminum

#### **RATINGS**

cETLus Wet Location ADA





# ADDITIONAL

SLOPE:

RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



	Job Name:	Job Type:
	Quantity:	Comments