



PRODUCT DESCRIPTION

Inconspicuously recessed within its cylindrical house, an extending arm transforms this surface mounted light fixture into an adjustable spotlight. Simply unthread the top half along the seam to extend the frame length and swing the fixture into position. Twist the lens on the face of this fixture to adjust its beam angle spread. Available in Black and White and two apertures that include a mud-in ring for an even cleaner installation.

FINISHES OPTION

- Black (BK)
- White (WT)

MATERIAL

Aluminum, Glass

RATINGS

cETLus  
Dry Location  
Energy Star  
CA Title 24



ADDITIONAL


RATED LIFE 25000 Hours  
OPERATING TEMPERATURE:  
-20°C (-4°F), 40°C (104°F)

MEASUREMENTS

- DIMENSION : 5.25" L x 5.25" W x 3.25" H
- CANOPY : 5.25" W x 0.25" H x 5.25" L
- HANGING WEIGHT : 0.88 lb

LAMPING

- INPUT VOLTAGE : 120-277V
- LUMENS : 1,200 Rated (1,030 Del.)
- BULB : 12W LED DC Integrated , 12W Total
- BULB INCLUDED : (Integrated)
- DIMMABLE : Triac or ELV at 120V
- CRI : 90 CRI
- COLOR\_TEMP : 3000K



Always consult a qualified electrician before installing any lighting product.

STUDIO•M

Modifications or Customizations: Please email [contract@studiomlighting.com](mailto:contract@studiomlighting.com)  
Sample Request: Please email [order@studiomlighting.com](mailto:order@studiomlighting.com) with subject line  
"Sample Order\_ [Project Name] / [Specifier/Designer]"  
All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments