

Job Name:

Job Type:\_

Quantity:

Comments:

# **PRODUCT DESCRIPTION**

This classic cylinder design has been made ultra-thin intending its use in applications requiring ADA compliance. The sconce casts generous lighting both upwards and downwards using dedicated, high-powered LED. Concealed within the frame, there is a range voltage 120-277V LED driver making this a great option for light commercial as well as residential applications. Available in Matte Black, Architectural Bronze and White outdoor powder coat finishes. For Dark Sky applications, make use of the optional Dark Sky Cap available.



# MEASUREMENTS

CANOPY HANGING WEIGHT

LAMPING INPUT VOLTAGE LUMENS BULB BULB INCLUDED DIMMABLE CRI COLOR\_TEMP : 5.25" W x 15.25" H : 5.25" W x 0.25" H x 5.25" L : 1.98 lb

: 120-277V

- : 700 Rated (620 Del.)
- : 7W LED DC Integrated , 7W Total
- : (Integrated)
- : Triac or ELV at 120V
- : 90 CRI
- : 3000K

## **FINISHES OPTION**



White (WT)

#### MATERIAL Aluminum, Glass

# RATINGS

cETLus Damp Location Energy Star CA Title 24



### ADDITIONAL

RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order\_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments