Reeds | SM151011CRGLD

Job Name:_____


Job Type:_____





PRODUCT DESCRIPTION

Reeded glass tubes are paired with ribbed aluminum LED housings in your choice of Gold or Matte Black finishes. The interior frosted glass diffusers soften the high-powered LED boards concealed within. The low-voltage light sources are driven by a commercially rated range voltage LED drivers with universal dimming, allowing them to be used in both residential and decorative commercial or hospitality applications. ADA compliant sconces are a welcome companion to the series as well as the fully metal stem hung pendant option designed without glass and uses a JA8 Listed LED GU10 lamp instead of dedicated LED.



*max overall height

DIMENSION MAX OAH CANOPY HANGING WEIGHT LAMPING

MEASUREMENTS

INPUT VOLTAGE LUMENS BULB BULB INCLUDED DIMMABLE

CRI COLOR_TEMP : 2.25" L x 2.25" W x 17" H : 140" OAH : 4.75" W x 1.5" H x 4.75" L : 2 lb

:120-277V

- : 500 Rated (400 Del.)
- : 5W LED PCB Integrated , 5W Total
- : (Integrated)
- : Only at 120V
- : 90 CRI : 3000K

FINISHES OPTION



GLASS Clear Ribbed 144

MATERIAL Aluminum

RATINGS CETLUS





ADDITIONAL

SLOPE: 30 RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments