






# PRODUCT DESCRIPTION

A central, cylinder diffuser of opal white acrylic diffuses LED lighting within a cavity of thin ribbed glass of various lengths. Both imaginative and functional, the bright pendants encase an additional down light recessed within a Polished Chrome, Naturally Aged Brass or Matte Black housing casting light downward.



# MEASUREMENTS

DIMENSION : 1.5" L x 1.5" W x 10.75" H
MAX OAH : 133.25" OAH

CANOPY : 4.75" W x 1.75" H x 4.75" L

HANGING WEIGHT : 1.98 lb

LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 600 Rated (450 Del.)

BULB : 7.5W LED PCB Integrated, 8W Total
BULB INCLUDED : (Integrated)

 DIMMABLE
 : Universal 3-in-1

 CRI
 : 90 CRI

 COLOR\_TEMP
 : 3000K

### **FINISHES OPTION**

Black (BK)

Natural Aged Brass (NAB)

Polished Chrome (PC)

#### **GLASS**

Clear Ribbed 144

#### MATERIAL

Steel, Aluminum, Glass

## **RATINGS**

cETLus Dry Location



Job Type: Comments



### **ADDITIONAL**

RATED LIFE 35000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com

Quantity:

Job Name: