






PRODUCT DESCRIPTION

A geometrical frame constructed of Black tubing, fitted with machined aluminum caps with clear acrylic diffusers. Housed in the caps are integrated LED which project diffused light in all directions.



MEASUREMENTS

DIMENSION MAX OAH CANOPY HANGING WEIGHT

LAMPING

INPUT VOLTAGE LUMENS BULB

BULB INCLUDED DIMMABLE

CKI

COLOR_TEMP

: 30" L x 30" W x 24" H

: 67.75" OAH

: 7" W x 1.5" H x 7" L

: 8.14 lb

: 120V

: 3,040 Rated (1,650 Del.)

: 2.7W LED PCB Integrated , 38W Total

: (Integrated)

: ELV or Triac CL

: 90 CRI

: 3000K

FINISHES OPTION



Black / Brushed Aluminum (BKAL)

GLASS

Clear Acrylic 75

MATERIAL

Aluminum, Steel, Acrylic

RATINGS

cETLus Dry Location



ADDITIONAL

SLOPE: 15 RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Job Name:	Job Type:
Quantity:	Comments