
Nodes | SM253512BK








PRODUCT DESCRIPTION

Introducing a new take on the now classically modern LED ring, large illuminated spheres act as "nodes" to support the tapered aluminum channel while also providing additional down light. Featuring a CCT selectable switch, the collection conveniently allows end users to select from warmer white light to energizing bright white lighting in 5 color temperature options. The convenient functionality is matched with its performance, meeting California's JA8 Title 24 requirements. Rated to deliver higher lumens per watt and power sources that supports range voltage input and 3 in one dimming, this product is designed to meet the requirements of both home and commercial projects.



*max overall height

DIMENSION MAX OAH HANGING WEIGHT LAMPING INPUT VOLTAGE LUMENS

MEASUREMENTS

BULB **BULB INCLUDED** DIMMABLE CRI COLOR_TEMP

: 24" L x 24" W x 2.75" H : 110" OAH : 3.12 lb

: 120-277V : 2,800 Rated (2,450 Del.) : 35W LED CCT Select PCB , 35W Total : (Integrated) : 90 CRI : CCT SelectK

FINISHES OPTION



MATERIAL Aluminum, Steel

RATINGS Dry Location

CA Title 24



ADDITIONAL

SLOPE: **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments

StudioMlighting.com - 1.626.956.4209