
Quantity:



## **PRODUCT DESCRIPTION**

\*max overall height

Constructed of double thick aluminum which has a hammered interior finish polished so to not only be beautiful but multiply the lumen output. High polish enamel paints finish the exterior for the ultimate reflective surface. The larger sizes are fitted with commercial grade LED and multi-volt input drivers that dim with both ELV and 0-10V functions.



MEASUREMENTS DIMENSION MAX OAH CANOPY HANGING WEIGHT LAMPING

INPUT VOLTAGE LUMENS BULB BULB INCLUDED DIMMABLE CRI COLOR\_TEMP : 9" L x 9" W x 5" H : 126" OAH : 1" W x 1" H x 5.5" L : 1.65 lb

:120V

- : 950 Rated (480 Del.)
- : 10W LED DC Integrated , 10W Total : (Integrated)
- : ELV or Triac CL
- : 90 CRI
  - : 3000K

## **FINISHES OPTION**



MATERIAL Aluminum,Steel

## RATINGS CETLUS

Dry Location



## ADDITIONAL

SLOPE: RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order\_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments