






PRODUCT DESCRIPTION

Channels of Black are fused in an erratic fashion concealing a LED light source that emits a soft and even illumination to the surface below. Light intensity is adjustable down to 10% to allow for multiple room scene settings.



MEASUREMENTS

 DIMENSION
 : 34.75" L x 33" W x 10.25" H

 MAX OAH
 : 132" OAH

 CANOPY
 : 6" W x 1.5" H x 9.75" L

 HANGING WEIGHT
 : 7.7 lb

LAMPING

INPUT VOLTAGE : 120V LUMENS : 3,500 Rated (2,200 Del.)

BULB : 50W LED PCB Integrated , 50W Total

 BULB INCLUDED
 : (Integrated)

 DIMMABLE
 : ELV

 CRI
 : 80+ CRI

 COLOR_TEMP
 : 3000K

FINISHES OPTION



MATERIAL

Aluminum, Steel

RATINGS

cETLus Dry Location





ADDITIONAL

ADJUSTABLE SLOPE: 70 RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



Job Name:	Job Type:
Quantity:	Comments