






PRODUCT DESCRIPTION

Channels of Black are fused in an erratic fashion concealing a LED light source that emits a soft and even illumination to the surface below. Light intensity is adjustable down to 10% to allow for multiple room scene settings.



MEASUREMENTS DIMENSION MAX OAH CANOPY HANGING WEIGHT

LAMPING INPUT VOLTAGE LUMENS BULB BULB INCLUDED DIMMABLE CRI COLOR_TEMP : 34.75" L x 33" W x 10.25" H : 132" OAH : 6" W x 1.5" H x 9.75" L : 7.7 lb

: 120V : 3,500 Rated (2,200 Del.) : 50W LED PCB Integrated , 50W Total : (Integrated) : ELV : 80+ CRI

: 3000K



Black (BK)

MATERIAL Aluminum, Steel

RATINGS CETLus Dry Location



ADDITIONAL

ADJUSTABLE SLOPE: 70 RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments