






PRODUCT DESCRIPTION

Channels of Black are fused in an erratic fashion concealing a LED light source that emits a soft and even illumination to the surface below. Light intensity is adjustable down to 10% to allow for multiple room scene settings.



MEASUREMENTS

DIMENSION : 34.75" L x 33" W x 10.25" H MAX OAH : 132" OAH CANOPY : 6" W x 1.5" H x 9.75" L HANGING WEIGHT : 7.7 lb

LAMPING

INPUT VOLTAGE : 120V **LUMENS** : 3,500 Rated (2,200 Del.)

BULB : 50W LED PCB Integrated , 50W Total

BULB INCLUDED : (Integrated) : ELV DIMMABLE

: 90 CRI COLOR_TEMP : 3000K

FINISHES OPTION



MATERIAL

Aluminum, Steel

RATINGS

cETLus Dry Location





ADDITIONAL

ADJUSTABLE SLOPE: 70 RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com
Sample Request: Please email order@studiomlighint.com with subject line
"Sample Order_ [Project Name] / [Specifier/Designer]"
All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments