Quantity:\_



## **PRODUCT DESCRIPTION**

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Choose from a variety of sizes, shapes that are sharply angled or smoothly sloping, and various photocell and motion sensor options. Also available with enabled switch to toggle between 5 light Color Temperature settings, this popular sconce has even more versatility. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor-rated powder coat finishes.

2.75″[ <sub>\*нсо</sub>[ 5.5″

\*height from center of outlet to the top of the fixture



LAMPING INPUT VOLTAGE LUMENS BULB

MEASUREMENTS

HANGING WEIGHT

DIMENSION

BACK PLATE

BULB INCLUDED DIMMABLE CRI COLOR\_TEMP LIGHTING\_DIRECTION : 5.5" W x 5.5" H x 4" Ext : 5.5" W x 5.5" H x 2.75" HCO

- : 120-277V : 1,270 Rated (820 Del.) : 15W LED PCB Integrated , 15W Total
- : (Integrated)

: 2.03 lb

- : Y

: 90 CRI : 3000K : Down

cETLus Wet Location ADA DARKSKY



FINISHES OPTION

Black (BK)

Silver (SV)

Aluminum,Glass

MATERIAL

RATINGS

Architectural Bronze (ABZ)

## ADDITIONAL

INSTALL UP/DOWN: UP PHOTOCELL OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order\_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments