


PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Either sharply angled or smoothly sloping, this discreet architectural light source is also available with various photocell and motion sensor options. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor rated powder coat finishes.



*height from center of outlet to the top of the fixture

MEASUREMENTS

DIMENSION : 5.5" W x 7" H x 4" Ext **BACK PLATE** : 4.25" HCO

HANGING WEIGHT : 2.31 lb

LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 1,050 Rated (750 Del.) BULB : 15W LED DC Integrated, 15W Total

BULB INCLUDED : (Integrated)

DIMMABLE : Triac or ELV at 120V

CRI : 90 CRI COLOR_TEMP : 3000K LIGHTING_DIRECTION : Down

Always consult a qualified electrician before installing any lighting product.

FINISHES OPTION

Architectural Bronze (ABZ)

Black (BK)

Silver (SV)

MATERIAL

Aluminum

RATINGS

cETLus Wet Location ADA







ADDITIONAL

INSTALL UP/DOWN: Down SLOPE: RATED LIFE 25000 Hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Modifications or Customizations: Please email contract@studiomlighing.com

Job Name:	Job Type:
Quantity:	Comments