Quantity:_

PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Choose from a variety of sizes, shapes that are sharply angled or smoothly sloping, and various photocell and motion sensor options. Also available with enabled switch to toggle between 5 light Color Temperature settings, this popular sconce has even more versatility. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor-rated powder coat finishes.

2.75″ 5.5″ 5.5′



*height from center of outlet to the top of the fixture

DIMENSION BACK PLATE HANGING WEIGHT LAMPING INPUT VOLTAGE

MEASUREMENTS

LUMENS BULB BULB INCLUDED DIMMABLE CRI COLOR_TEMP

: 5.5" W x 5.5" H x 4" Ext : 5.5" W x 5.5" H x 2.75" HCO

- : 120-277V : 1,500 Rated (540 Del.)

- LIGHTING_DIRECTION

: 0.9 lb

- : 15W LED DC Integrated , 15W Total
- : (Integrated)
- : Triac
- : 90 CRI : 3000K
 - : Down

FINISHES OPTION



MATERIAL AluminumGlass

RATINGS cETLus Wet Location

ADA



ADDITIONAL

INSTALL UP/DOWN: Down SLOPE: RATED LIFE 25000 Hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments