
PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Either sharply angled or smoothly sloping, this discreet architectural light source is also available with various photocell and motion sensor options. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor rated powder coat finishes.



*height from center of outlet to the top of the fixture

MEASUREMENTS

DIMENSION : 5.5" W x 5.5" H x 4" Ext **BACK PLATE** : 5.5" W x 5.5" H x 2.75" HCO

HANGING WEIGHT : 0.9 lb

LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 1,500 Rated (540 Del.)

: 15W LED DC Integrated, 15W Total

BULB INCLUDED : (Integrated) DIMMABLE : Triac CRI : 90 CRI COLOR_TEMP : 3000K LIGHTING_DIRECTION : Down

FINISHES OPTION

Architectural Bronze (ABZ)

Black (BK)

Silver (SV)

MATERIAL

AluminumGlass

RATINGS

cETLus Wet Location ADA







ADDITIONAL

INSTALL UP/DOWN: Down SLOPE: RATED LIFE 25000 Hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



Modification	ns or Customizat	ions: Please em	ail contract@s	tudiomlighing.co	om
Sample Rea	uest: Please em	ail order@studio	mlighint.com	with subject line	
"Sample Ord	der_ [Project Na	me] / [Specifier,	(Designer)"		
All samples	are subject to St	udio M approve	al and must sho	ow proof of proje	ect and/or explanation.

Job Name:	Job Type:
Quantity:	Comments