Job Type:_



PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Choose from triangular or spherical profiles as they discreetly extend from the wall. Available with a photocell option, these archetypal forms purposely blend into the architectural landscape creating safer spaces that shine light on locations of interest. Available in Black, Architectural Bronze, or Metallic Sliver





*height from center of outlet to the top of the fixture

MEASUREMENTS DIMENSION BACK PLATE

HANGING WEIGHT LAMPING INPUT VOLTAGE LUMENS

BULB BULB INCLUDED DIMMABLE CRI COLOR_TEMP LIGHTING_DIRECTION : 5.5" W x 5.5" H x 4" Ext : 5.5" W x 5.5" H x 2.75" HCO : 2.03 lb

- : 120-277V
 - : 1,270 Rated (820 Del.)
- : 15W LED PCB Integrated , 15W Total
- : (Integrated)
- : Only at 120V with ELV
- : 80 CRI
- - : Down

- - : 3000K

FINISHES OPTION



MATERIAL Die Cast Aluminum

RATINGS

cETLus Wet Location For Outdoor ADA DARKSKY



ADDITIONAL

Job Type:

Comments

INSTALL UP/DOWN: Up/Down SLOPE: OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.

Job Name:

Quantity:



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/

I/or explanation. StudioN	VIII	gn	m	g
---------------------------	------	----	---	---

ctudio Miabti a.com - 1.626.956.4209