

PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Choose from a variety of sizes, shapes that are sharply angled or smoothly sloping, and various photocell and motion sensor options. Also available with enabled switch to toggle between 5 light Color Temperature settings, this popular sconce has even more versatility. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor-rated powder coat finishes.

MEASUREMENTS

DIMENSION : 7" W x 4.5" H x 3.5" Ext

BACK PLATE : 2.25" HCO HANGING WEIGHT : 1.51 lb

LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 880 Rated (820 Del.)

BULB : 15W LED PCB Integrated, 15W Total

BULB INCLUDED : (Integrated)

DIMMABLE : Only at 120V with ELV

CRI : 80 CRI
COLOR_TEMP : 3000K
LIGHTING_DIRECTION : Down

FINISHES OPTION



MATERIAL

Aluminum +Acrylic

RATINGS

cETLus Wet Location ADA







ADDITIONAL

INSTALL UP/DOWN: Down SLOPE: PHOTOCELL RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Job Name:	Job Type:
Quantity:	Comments