Job Type:_





PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Choose from triangular or spherical profiles as they discreetly extend from the wall. Available with a photocell option, these archetypal forms purposely blend into the architectural landscape creating safer spaces that shine light on locations of interest. Available in Black, Architectural Bronze, or Metallic Sliver



MEASUREMENTS DIMENSION

BACK PLATE HANGING WEIGHT LAMPING INPUT VOLTAGE LUMENS BULB BULB INCLUDED DIMMABLE CRI

COLOR_TEMP LIGHTING_DIRECTION : 7" W x 4.5" H x 3.5" Ext : 2.25" HCO : 1.4 lb

: 120-277V

- : 120-277V : 880 Rated (820 Del.)
- : 15W LED PCB Integrated , 15W Total : (Integrated)
- : Only at 120V with ELV
- : 80 CRI
- : 3000K
- : Down

RAT CETL Wet For



ADDITIONAL

INSTALL UP/DOWN: Down RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments

StudioMlighting.com - 1.626.956.4209



FINISHES OPTION

MATERIAL

Aluminum +Acrylic

RATINGS

cETLus Wet Location For Outdoor ADA