Job Type:_



PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Choose from a variety of sizes, shapes that are sharply angled or smoothly sloping, and various photocell and motion sensor options. Also available with enabled switch to toggle between 5 light Color Temperature settings, this popular sconce has even more versatility. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor-rated powder coat finishes.

| 8" | | 4" |
|----|----|----|
| | Q" | |
| | 9 | 4 |

*height from center of outlet to the top of the fixture

BACK PLATE HANGING WEIGHT LAMPING INPUT VOLTAGE LUMENS BULB BULB INCLUDED DIMMABLE CRI COLOR_TEMP LIGHTING_DIRECTION

MEASUREMENTS

DIMENSION

: 9" W x 8" H x 4" Ext : 4" HCO : 3.08 lb

- : 120-277V : 2,000 Rated (1,500 Del.) : 20W LED DC Integrated , 20W Total : (Integrated)
- : Triac or ELV at 120V
- : 90 CRI : 3000K
 - : Down

FINISHES OPTION



MATERIAL Aluminum

RATINGS cETLus Wet Location ADA



ADDITIONAL

INSTALL UP/DOWN: Down SLOPE: RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project a

| approval and must show proof of proje- | |
|--|--|
| | |
| | |
| | |

| Job Name: | Job Type: |
|-----------|-----------|
| Quantity: | Comments |