Comments:

PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Choose from a variety of sizes, shapes that are sharply angled or smoothly sloping, and various photocell and motion sensor options. Also available with enabled switch to toggle between 5 light Color Temperature settings, this popular sconce has even more versatility. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor-rated powder coat finishes.

MEASUREMENTS DIMENSION BACK PLATE HANGING WEIGHT	: 5" W x 12" H x 4" Ext : 5" W x 12" H x 6" HCO : 3.3 lb
LAMPING INPUT VOLTAGE LUMENS BULB BULB INCLUDED DIMMABLE CRI COLOR_TEMP LIGHTING_DIRECTION	: 120-277V : 2,500 Rated (1,150 Del.) : 25W LED DC Integrated , 25W Total : (Integrated) : Triac or ELV at 120V : 90 CRI : 22-27-30-35-40K : Down

FINISHES OPTION



Silver (SV)

MATERIAL Aluminum, Glass

RATINGS CETLUS

Wet Location ADA



ADDITIONAL

INSTALL UP/DOWN: Down SLOPE: RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Job Name: Job Type: Quantity: Comments

Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

StudioMlighting.com - 1.626.956.4209