

LENCIR LED 15" | SURFACE MOUNT

SM567736


- Edge-Lit Technology, evenly distributed light
- Available in 3000K color temperature (See 57737 for 4000K)
- Available in Bronze (BZ), Satin Nickel (SN), and White (WT)
- Dimmable with ELV dimmer at 120V
- 120-277 Input Voltage
- Energy Star listed
- Approved for use in closets and storage spaces
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Easy to install: Fits 4" Outlet Box
- Not recommended for pancake box
- Suitable for Wet location
- ETL/cETL IP65

Job Name:	Job Type:
Quantity:	Comments:



PRODUCT DESCRIPTION

Lencir was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Lencir brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.



MEASUREMENTS

DIMENSIONS	: 15"L x 15"W x 0.5"H	
HANGING WEIGHT	: 3.53 lb	MAX OH : 0.5"
HCO	: 0.5"	MIN OH : 0.5"
BP Width	: 4.1"	

LAMPING

INPUT VOLTAGE	: 120-277V
LUMENS	: 2500 Rated (2200 Del.)
BULB	: 36W PCB LED (Integrated)
DIMMABLE	: Dimmable with ELV Dimmer at 120V
CRI	: 90+
COLOR TEMPERATURE	: 3000K

FINISHES OPTIONS:

- White (WT)
- Bronze (BZ)
- Satin Nickel (SN)



MATERIAL:

- Aluminum
- PMMA Acrylic Diffuser

RATINGS:

- ETL/cETL IP65
- Wet Location
- Energy Star
- Closets Rated: NEC 410.8 & 410.16



ADDITIONAL:

- RATED LIFE: 50,000 Hours
- OPERATING TEMP: -20° C (-4°), 40°C (104°F)
- PHOTOMETRIC: Report Found Online

Always consult a qualified electrician before installing any lighting product

STUDIO•M

For Modifications or Customizations, please email contract@studiomlighting.com
For Sample Request, please email order@studiomlighting.com with subject line: "Sample Order_[Project Name]/[Specifier/Designer]"
All Samples are subject to Studio M approval and must show proof of project and/or explanation.