

LENCIR LED PENDANTS 15" | SURFACE MOUNT

SM567836/ SM567838

- New models feature 120-277V input
- Ultra thin 0.5" H
- Dimmable with Triac Dimmer, CRI 90+
- 50,000 Hours Rated life, 3000K
- Suitable for Damp location
- ETL/cETL IP65

Job Name:	Job Type:
Quantity:	Comments:



57836



57838

PRODUCT DESCRIPTION

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.

FINISHES OPTIONS:

- White (WT)
- Bronze (BZ)
- Satin Nickel (SN)



MEASUREMENTS

DIMENSIONS	: 15"L x 15"W x 0.5"H
CANOPY	: 6"L x 6"W x 1.5"H
OAH	: 122"H
WIRE LENGTH	: 120"L

LAMPING

INPUT VOLTAGE	: 120-277V
LUMENS	: 2520 Rated (2200 Del.)
BULB	: 36W PCB LED (Integrated)
DIMMABLE	: Dimmable with ELV Dimmer at 120V
CRI	: 90+
COLOR TEMPERATURE	: 3000K

MATERIAL:

Aluminum
PMMA Acrylic Diffuser

RATINGS:

ETL/cETL IP65
Damp Location
Dimmable



ADDITIONAL:

RATED LIFE: 50,000 Hours
OPERATING TEMP: -20° C (-4°), 40°C (104°F)
PHOTOMETRIC: Report Found Online

Always consult a qualified electrician before installing any lighting product

STUDIO•M

For Modifications or Customizations, please email contract@studiomlighting.com
For Sample Request, please email order@studiomlighting.com with subject line: "Sample Order_[Project Name]/[Specifier/Designer]"
All Samples are subject to Studio M approval and must show proof of project and/or explanation.