SM660003SN

- FTL/CFTL
- Title 20 listed
- LED 3000K
- Suitable for Dry location
- Wall mountable (remote control included)

Job Name:	Job Type:
Quantity:	Comments:





PRODUCT DESCRIPTION

The Counter fandelier is functional art at its finest. Bold, sleek and contemporary, the Counter is sure to be the focal point of any kitchen or living area. The fan blades, contained within a cage of four steel curved bars with LED integrated light strips, silently circulate the air at the speed of your preference. The Counter fandelier offers modern aviation appeal, solid construction, and a beautiful Satin Nickel finish.

- Always consult a qualified electrician before installing any lighting product
- Installation Requirements:

Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding at least 35 lbs





MEASUREMENTS

DIMENSIONS : 34.5"D x 18.25"H CANOPY : 7"D x 2.75"H HANGING WEIGHT : 15.93 lb

: 3 Blades with 22" span **BLADE**

BLADE PITCH : Varying BLADE TO CEILING : 11"H

LAMPING

INPUT VOLTAGE : 120V

LUMENS : 9315 Rated (3640 Del.) BULB : 56W PCB LED (Integrated)

DIMMABLE : Yes **CRI** : 80+ COLOR TEMP : 3000K MOTOR TYPE : DC Motor

AIRFLOW

SPEEDS AIRFLOW CFM : 5057 **ELECTRICITY USE** · 31 90W AIRFLOW EFFICIENCY: 158.5

FINISHES OPTIONS:

Satin Nickel (SN)

MATERIAL:

Steel Aluminum

Polypropelene Fan Blades

INCLUDES

- Wall Mountable Remote Control
- 1 x 8" Downrod

DOWNROD OPTIONS

- 18" (FRD0118SN)
- 24" (FRD0124SN)
- 30" (FRD0130SN)
- 36" (FRD0136SN)

RATINGS:

FTL CFTL Dry Location Title 20





ADDITIONAL:

RATED LIFE: 35,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F)

LIGHTING DIRECTION: Up

