TUSCANY | FANDELIER SM660015DWIO

• ETL/cETL


- Title 20 listed
- LED 3000K
- Suitable for Damp location
- Wall mountable (remote control included)



PRODUCT DESCRIPTION

The Tuscany Fandelier's Mediterranean appeal and antique flair makes it perfect for brightening a space while adding a touch of style and beauty. Picturesque and functional, the Tuscany Fandelier with its ornate metalwork and Driftwood band provide an elegant accent to any rustic, classic or traditional decor. This Fandelier features a hand-painted Driftwood finish along a band that conceals its integrated LED light source, and it is complemented by Iron Ore metal accents. It is ideal for use in any indoor or outdoor dining and living areas.

- Always consult a qualified electrician before installing any lighting product
- Installation Requirements:
- Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding at least 50 lbs





MEASUREMENTS

 DIMENSIONS
 : 30.25"D x 25.75"H

 CANOPY
 : 7"D x 2.75"H

 HANGING WEIGHT
 : 36.63 lb

 BLADE
 : 3 Blades with 22" span

 BLADE PITCH
 : Varying

 BLADE TO CEILING
 : 17.25"H

:120V

: Yes : 80+

: 3000K

: DC Motor

: 3936 Rated (2000 Del.)

: 46W PCB LED (Integrated)

LAMPING

INPUT VOLTAGE LUMENS BULBS DIMMABLE CRI COLOR TEMP MOTOR TYPE

AIRFLOW

SPEEDS : 6 AIRFLOW CFM : 5057 ELECTRICITY USE : 31.90W AIRFLOW EFFICIENCY: 158.5

STUDIO•M

For Modifications or Customizations, please email contract@studiomlighting.com

For Sample Request, please email order@studiomlighting.com with subject line: "Sample Order_[Project Name]/[Specifier/Designer]" All Samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments:

FINISHES OPTIONS:

Driftwood / Iron Ore (DWIO)

MATERIAL:

Steel Polypropelene Fan Blades Polyresin Aluminum

INCLUDES

- Wall Mountable Remote Control
- 1 x 13.375" Downrod

DOWNROD OPTIONS

- 18" (FRD0118IO)
- 24" (FRD0124IO)
- 30" (FRD0130IO)
- 36" (FRD0136IO)

RATINGS:

ETL cETL Damp Location Title 20



ADDITIONAL: RATED LIFE: 35,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) LIGHTING DIRECTION: Down