

## **PRODUCT DESCRIPTION**

Linear EE collection's commercial grade energy efficient lighting features linear frames of metal finished in Satin Nickel and White acrylic diffusers. High Power Factor ballasts allow for commercial applications and the fluorescent light source ensure low maintenance and energy cost savings. Specific styles of Linear EE are also available with a LED light source in the Linear LED collection.



## **MEASUREMENTS**

DIMENSION **BACK PLATE** HANGING WEIGHT

LAMPING

INPUT VOLTAGE LUMENS

BULB

**BULB INCLUDED** 

DIMMABLE

: 6.02 lb

: 120V : 4,300 Rated

: 36" W x 6" H x 4" Ext

: 25W Fluorescent Med Bi Pin T8, 50W Total

: 2.74" W x 35.17" H x 2.25" HCO

: (Not Included)

: No

## **FINISHES OPTION**



**GLASS** 

White WT

MATERIAL

Metal

**RATINGS** 

cETLus Damp Location CA Title 24 ADA







## **ADDITIONAL**

INSTALL UP/DOWN: All **INCANDESCENT WATTS: 436** RATED LIFE 10000 Hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Quantity: Comments	Job Name:	Job Type:
	Quantity:	Comments